

LED HIGH BAY G4

APPLICATIONS : Warehouse, Plant, Supermarket, Storage Room, Workshop, Stadium etc.



Design by Japanese




- ✓ HIGH QUALITY LED CHIP 169 LM/W
- ✓ HIGH PERFORMANCE AND DURABLE
- ✓ EXCELLENT HEAT SINK
- ✓ ENERGY SAVING MORE THAN 50%
- ✓ LONG LIFE SPAN




SPECIFICATION

PRODUCT MODEL	HB04-120N
POWER	120W
LUMEN	20,280 LM
LUMEN/WATT	169 LM/W
INPUT VOLTAGE	AC120-277V, 50-60 HZ
SURGE PROTECTION	SURGE IMMUNITY LINE-EARTH 4KV, LINE-LINE 4KV
POWER FACTOR	PF > 0.95 +/- 2%
OPERATION TEMPERATURE	-40°C TO 70°C
COLOR TEMPERATURE (CCT)	3,000 / 5,000 / 6,500 K
COLOR RENDERING (RA)	CRI > 80
MATERIAL	ALUMINIUM + CU
BEAM ANGLE	60° / 90° / 120°
IP RATE	IP 65
THDI (%)	< 10%
LIFE TIME	50,000 HRS
DIMENSION (ØAXB MM)	Ø460X390
WEIGHT	4.3 KG
FUNCTION	ISOLATED 3 IN 1 DIMMING (1-10V / PWM / RESISTOR)


DIMENSION




PHOTOMETRIC DATA



BEAM ANGLE 60°



BEAM ANGLE 90°



BEAM ANGLE 120°



LEDsave

LEDsave (THAILAND) CO., LTD.

15/16 Moo18 Bangphli-Yai, Bangphli, Samutprakan 10540

TEL. 02-045-4768-9

FAX. 02-045-3884-5

www.facebook.com/LEDsave

@ledsave

admin@ledsave.co.th

www.ledsave.co.th



LINE : @LEDsave